

MicroVantage™ HCE Series

High Capacity Polyester Pleated Filter Cartridges

MicroVantage
Ultra Premium Filter Series

Request a Quote Today!



- 90% efficiency polyester pleated media
- High capacity stable pore structure
- Optimized for retention and excellent flow rates
- Heavy duty components protect pleated media and strengthens structural stability
- Manufactured in state-of-the-art clean room environment for high purity applications
- Complies with FDA CFR criteria for food & beverage contact
- Available in a variety of end cap configurations to fit most filter housings
- Thermal bonded and produced in standard lengths up to 40 inches

Applications

Ink	Paints & Coatings
Adhesives	Beer & Wine Pre-filtration
Cosmetics	RO Prefilters
Viscous Fluids	Process Water

Specifications and Operating Parameters

Pore Sizes

0.5, 1.0, 3.0, 5.0, 10, 25 and 50 micron

Nominal Lengths

10" (25.4 cm), 20" (50.8 cm), 30" (76.2 cm), 40" (101.6 cm)

Outside Diameter

2.67" (6.78 cm)

Gaskets/O-rings

Silicone, EPR, Viton, Buna, Teflon Encapsulated Viton,
Teflon Encapsulated Silicone

Materials of Construction

Filter Media: Polyester
Outer Cage Polypropylene
Inner Core: Polypropylene
End caps: Polypropylene

Maximum Operating Temperature

Standard Materials: 176°F (80°C)

Recommended Change-out Differential Pressure

25-30 psid (1.72 – 2.07 bar)


Maximum Differential Collapse Pressure

Forward: 70 psid @ 70°F (4.8 bar @ 21° C)
50 psid @ 176°F (3.4 bar @ 80° C)

Sanitization and Sterilization

Hot water at 194°F (90°C) @ max 3 psid for 30 minutes
In-line steam at 257°F (125°C) @ max 3 psid for 30 minutes
Autoclavable at 257°F (125°C) for 30 minutes

Flow vs. Pressure Drop



GALLONS PER MINUTE

This chart represents typical water flow per 10" cartridge length. The test fluid is water at ambient temperature. Extrapolation for multiple elements tends to be linear, but as flows increase the Δ of the housing becomes more apparent



Rigid High Capacity Pleats

Ordering Guide (Example: HCE5-20S5E-HT)

HCE	5	—	20	S5	E	—	HT
PRODUCT CODE	MICRON		LENGTH	END CAP CONFIGURATION	GASKET/O-RING		OPTIONS
HCE	0.5 1.0 3.0 5.0 10 25 50		10" 20" 30" 40"	S1 = DOE S3 = 222 w/ Fin End S4 = 222 w/ Flat End S5 = 226 w/ Fin End S6 = 226 w/ Flat End S7 = Internal O-ring with Recessed Plug	S = Silicone E = EPR V = Viton B = Buna T/V = Teflon encapsulated Viton T/S = Teflon encapsulated Silicone		*HT = High Temp Components S = SS Insert Reinforcing Ring

*Maximum operating temperature 205°F (96°C)

Sanitary Filter Housings & Accessories

Shelco offers a full line of sanitary and High Purity filter housings and accessories to meet your most critical applications.



COMMERCIAL FILTRATION SUPPLY

Authorized MAHLE-Nowata Distributor & Representative

For pricing and information please call
Commercial Filtration Supply at (855)-236-0467

Visit us Online at: www.commercialfiltrationsupply.com
for more filtration products.