

Request a Quote Today!

NP-RFG20BB

Radial Flow Filter Cartridge

neo•PURE™



Contaminants Reduced:

- Chlorine Taste and Odor
- Dirt
- Rust
- Sediment



*Residential/Commercial
Filtration Applications*

Standard Features

- Manufactured in China
- Environmentally-friendly coconut shell granular activated carbon (GAC) filter
- Ideal for point-of-entry (POE) and other high flow rate application
- Compatible with Pentek® RFC20-BB, 155247-43, Watts® MAXRFL-FF20
- Drop-in cartridge style

Product Specifications

Filter Media

Coconut shell granular activated carbon (GAC)

Micron Rating (Nominal)

25 microns

Dimensions

4-1/2" dia. x 20"

Capacity

40,000 gallons

Operating Temperature

40 to 100°F (4.4 to 37.8°C)

Operating Pressure

30 to 100 psi

Maximum Flow Rate

6 gpm

Change Frequency

6 months

WARNING:

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

**COMMERCIAL
FILTRATION SUPPLY**

Authorized MAHLE-Nowata Distributor & Representative

For pricing and information please call
Commercial Filtration Supply at (855)-236-0467

Visit us Online at: www.commercialfiltrationsupply.com
for more filtration products.